




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁵: C07C 17/38, 19/08, B01D 3/14	A1	(11) International Publication Number: WO 94/19301 (43) International Publication Date: 1 September 1994 (01.09.94)
(21) International Application Number: PCT/US94/01117 (22) International Filing Date: 31 January 1994 (31.01.94) (30) Priority Data: 08/023,827 23 February 1993 (23.02.93) US (71) Applicant: ALLIEDSIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: CLEMMER, Paul, Gene; 128 Royal Parkway W., Williamsville, NY 14221 (US). TUNG, Hsueh, Sung; 16 Vassar Drive, Getzville, NY 14068 (US). SMITH, Addison, Miles; 80 Berryman Drive, Amherst, NY 14226 (US). (74) Agent: CRISS, Roger, H.; AlliedSignal Inc., Law Department (C.A. McNally), 101 Columbia Road, P.O. Box 2245R, Morristown, NJ 07962-2245 (US).		(81) Designated States: JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: PURIFICATION OF A COMPONENT OF A BINARY AZEOTROPE



(57) Abstract

The invention generally relates to a process for the purification of a component of a binary azeotrope in which the composition of the azeotrope changes by about 10 mole percent with pressure comprising: a) subjecting a binary azeotrope to a distillation step in which most of one of the binary components is removed as distillate (distillate 1) with the bottoms (bottoms 1) enriched in the other component; b) subjecting distillate 1 to at least one additional distillation step conducted at a different pressure in which most of the component recovered as bottoms 1 is removed as distillate 2 with the bottoms 2 enriched in the component enriched in distillate 1; c) optionally repeating step (b) as many times as desired; and d) recovering the desired purified component. The invention is particularly useful in the purification of pentafluoroethane in a pentafluoroethane/chloropentafluoroethane azeotrope.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

PURIFICATION OF A COMPONENT OF A BINARY AZEOTROPE

5

BACKGROUND OF THE INVENTION

Pentafluoroethane or HFC-125 is a stratospherically safe
10 substitute for dichlorodifluoromethane (CFC-12) and chloropenta-
fluoroethane (CFC-115) in refrigerant and sterilant gas
applications. Methods for the production of HFC-125 are well
known in the art. See, for example, USP 3,755,477. The problem
with these processes is that they produce large amounts of CFC-115
15 as a by-product which must be removed in order to comply with the
Program for Alternative Fluorocarbon Toxicity Testing (PAFT)
guidelines for product purity. PAFT requires that no more than
0.5% CFC-115 can be present in HFC-125. In addition, still lower
levels of CFC-115 (i.e., $<0.5\%$) are desirable to eliminate any
20 ozone depletion risk.

Because CFC-115 forms an azeotrope with HFC-125, see USP
3,505,233, it is hard to remove using conventional separation
techniques such as simple distillation. The art has therefore
25 looked to extractive distillation techniques to separate these
materials. See USP 5,087,329 which utilizes a 1 - 4 carbon
fluorocarbon which optionally contains hydrogen and/or chlorine
and has a boiling point of $-39^{\circ}\text{C} < \text{e.a.} < 50^{\circ}\text{C}$ to increase the
relative volatility of HFC-125 so that it can be more easily
30 removed from the mixture. The problem with extractive
distillation is that it adds cost and time, requiring yet another
distillation step to recover the extracting agent.

Applicants have discovered a process for the removal of CFC-
35 115 from HFC-125 which overcomes these drawbacks and results in
the production of high purity HFC-125 in high yield.

DESCRIPTION OF THE INVENTION

The invention preferably relates to a process for the purification of pentafluoroethane in a binary azeotrope of

5 pentafluoroethane and chloropentafluoroethane comprising:

(a) subjecting a mixture comprising pentafluoroethane and at least about 0.5 mole % chloropentafluoroethane to a distillation step in which most of one of pentafluoroethane or chloropentafluoroethane is removed as distillate (distillate 1) with the

10 bottoms (bottoms 1) enriched in the other component;

(b) subjecting distillate 1 to at least one additional distillation step conducted at a different pressure in which most of the component recovered as bottoms 1 is removed as distillate 2 with the bottoms 2 enriched in the component enriched in

15 distillate 1;

(c) optionally repeating step (b) as many times as desired;

and

(d) recovering purified pentafluoroethane.

20 The invention is not limited to the purification of pentafluoroethane. It is generally applicable to the purification of any component of a binary azeotrope in which the composition of the azeotrope changes by about 10 mole percent with pressure and comprises:

25 (a) subjecting a binary azeotrope to a distillation step in which most of one of the binary components is removed as distillate (distillate 1) with the bottoms (bottoms 1) enriched in the other component;

(b) subjecting distillate 1 to at least one additional
30 distillation step conducted at a different pressure in which most of the component recovered as bottoms 1 is removed as distillate 2 with the bottoms 2 enriched in the component enriched in distillate 1;

(c) optionally repeating step (b) as many times as desired;

35 and

(d) recovering the desired purified component.

We have discovered that by using the above-described novel
5 distillation technique, we are able to minimize the effect of the
CFC-115/HFC-125 azeotrope and produce high purity HFC-125 in high
yield.

It is well known in the art that the composition of an
10 azeotrope will vary with pressure. We discovered that the
composition of the CFC-115/HFC-125 azeotrope changes dramatically
(i.e., more than one would have predicted) with pressure.
Specifically, we discovered that when pressure is increased to
about 200 psia, the concentration of CFC-115 in the CFC-115/HFC-
15 125 azeotrope approaches zero.

As stated above, the novel distillation technique of the
invention is applicable to the purification of any component of a
binary azeotrope in which the azeotrope composition changes by
20 about 10 mole percent with pressure.

The purification of a component of a binary azeotrope, such
as HFC-125 in the HFC-125/CFC-115 azeotrope, via the novel
distillation technique of the invention may be accomplished by
25 using a single distillation column operating at low and high
pressure (or vice versa) with different batches or a series of
distillation columns (i.e., two or more) operating at several
different pressures. When a single distillation column is used,
the crude HFC-125 mixture containing CFC-115 may be fed, for
30 example, to a distillation column operating at high pressure. The
distillate is then collected and re-fed into the column now
cleaned and operating at low pressure. The purified HFC-125 is
then recovered from the bottom of the still. See Example 1.
Example 2 and Figure 1, exemplify the novel distillation
35 technique of the invention using two columns.

When two or more columns are used, they may be operated as a

-4-

batch or continuous distillation. Figure 1 is a schematic view of the novel distillation technique of the invention in which two distillation columns are used in a continuous distillation. In this figure, the distillate or overhead (3) from the low pressure column (C2) is recycled back to the high pressure column (C1). Alternately, the first distillation column may be operated at low pressure and the second column at high pressure. In this case, the distillate from the high pressure column is recycled to the low pressure column. When the novel distillation technique of the invention is used commercially, it is best to use it in the continuous operating mode in order to maximize the HFC-125 yield.

The precise configuration (i.e., whether the feed is first introduced into a high or low pressure column) depends upon the feed composition and process economics. The feed composition must contain less than the azeotropic amount of CFC-115 in order for the CFC-115 to be removed as distillate (overhead). For example, if the CFC-115 concentration in the feed is greater than the azeotropic composition in the low pressure column, then it will be necessary to introduce the feed into the high pressure column so that the majority of the CFC-115 can be removed quickly from the bottom of the high pressure column.

The pressure at which the distillations are conducted is preferably less than about 400 psia and greater than about 5 psia, more preferably less than about 300 psia and greater than about 10 psia, and most preferably less than about 250 psia and greater than about 15 psia. The distillations may for example be conducted at a pressure of from about 50 to about 400 psia and a pressure of from about 15 to about 35 psia, a pressure of from about 100 to about 300 psia and a pressure of from about 15 to about 25 psia, a pressure of from about 150 to about 250 psia and a pressure from about 15 to about 20 psia.

The pressure at which most of the HFC-125 can be removed as distillate is preferably about 50 to about 300 psia, more preferably about 100 to about 250 psia and most preferably about

-5-

150 to about 220 psia. The pressure at which most of the CFC-115 can be removed as distillate is preferably less than about 35 psia, more preferably less than about 25 psia and most preferably less than about 20 psia.

5

The temperature at which the distillation(s) is(are) conducted will depend on the pressure used.

10 The HFC-125 to be purified may be prepared by any process known in the art. See USP 3,755,477. Typically, known processes for the production of HFC-125 like that of USP 3,755,477 produce at least 2 mole % CFC-115 as a by-product.

15

EXAMPLE 1

Crude HFC-125 containing 98.5 mole % HFC-125, 1.2 mole % CFC-115 and about 0.3 mole % of other reaction products prepared by the fluorination of dichlorotrifluoroethane (i.e., 1,1-dichloro-2,2,2-trifluoroethane (HCFC-123) containing about 9 mole % 1,2-dichloro-1,2,2-trifluoroethane (HCFC-123a)) with anhydrous hydrogen fluoride in the presence of a chromia/alumina catalyst was charged to a distillation column consisting of an Inconel reboiler attached to a 2 inch diameter stainless steel column filled with 1/4" protruded ribbon packing made of Monel. A stainless steel condenser was mounted on top of the column. Chilled methanol was pumped to the condenser to provide cooling. The distillation column was operated at about 24.7 psia, a reflux temperature of about -38°C and a reboiler temperature of about -37°C.

30

Upon distillation, a distillate containing about 95 mole % HFC-125 and about 5 mole % CFC-115 was removed at a reflux ratio of about 20:1 until the reboiler CFC-115 content was reduced to about 0.3 mole %. The distillate was then fed back into the column and distilled again. This time, the pressure in the distillation column was raised to about 206.7 psia by heating the reboiler

35

-6-

using steam and lowering the condenser coolant flow. The reflux temperature was about 30°C and the reboiler temperature was about 40°C. The distillate from this second distillation had a composition of about 97/3 mole % HFC-125/CFC-115 respectively.

5

EXAMPLE 2

The following Example is performed using the set-up shown in Figure 1.

To a distillation column, C1, similar in structure to the distillation column of Example 1 is fed crude HFC-125 containing 20 mole % CFC-115 (see Table I, column F1) which is obtained by the hydrofluorination of HCFC-123 with anhydrous hydrogen fluoride in the presence of a chrome oxide catalyst. The distillation is conducted at 220 psia, a reflux temperature of about 28°C and a reboiler temperature of about 35°C. The overhead (1) contains relatively pure HFC-125 (96 mole %). Little CFC-115 is carried overhead as the azeotrope while the bottom (2) is rich in CFC-115. The overhead is then passed to a second distillation column, C2, similar in structure to C1, operated at low pressure, (i.e., 24.7 psia), a reflux temperature of about -38°C and a reboiler temperature of about -37°C. At low pressure, the amount of CFC-115 in the azeotrope increases dramatically. The azeotrope, now rich in CFC-115, is distilled over (3), while essentially pure HFC-125 (99.8 mole %) is removed as the bottoms (4). See Table I for an in depth description of the reaction conditions and mass balance information.

30

35

-7-

TABLE I

Heat and Material Balance Table							
5	Stream ID		F1	1	2	3	4
	Mole Flow	LBMOL/HR					
	G125		0.80	1.04	0.35	0.27	0.77
	G115		0.20	0.04	0.19	0.04	1.19 E-3
	Total Flow	LBMOL/HR	1.00	1.08	0.23	0.31	0.77
10	Total Flow	LB/HR	126.91	131.02	34.89	39.01	92.01
	Std. Vol Flow	FT³/HR	1.69	1.84	0.47	55.02	1.02
	Temp.	°C	26.00	31.32	41.48	-36.71	-36.32
	Pressure	PSIA	220.00	214.70	214.70	24.70	24.70

EXAMPLE 3

20 Crude HFC-125 containing 98.5 mole % HFC-125, 1.2
 mole % CFC-115 and about 0.3 mole % of other reaction
 products is prepared by the fluorination of
 dichlorotrifluoroethane (i.e., 1,1-dichloro-2,2,2-
 trifluoroethane (HCFC-123) containing about 9 mole %
 1,2-dichloro-1,2,2-trifluoroethane (HCFC-123a)) with
 25 anhydrous hydrogen fluoride in the presence of a
 chromia/alumina catalyst and is charged to a
 distillation column consisting of an Inconel reboiler
 attached to a 2 inch diameter stainless steel column
 filled with 1/4" protruded ribbon packing made of

-8-

Monel. A stainless steel condenser is mounted on top of the column. Chilled methanol is pumped to the condenser to provide cooling. The distillation column is operated at about 180 psia, a reflux temperature of about 20°C and a reboiler temperature of about 30°C.

Upon distillation, the distillate contains essentially pure HFC-125 (>99 mole %) while the bottom is enriched in CFC-115. The distillate is then fed back into the column and distilled at a pressure of about 35 psia (obtained by raising the condenser coolant flow), a reflux temperature of about -26°C and a reboiler temperature of about -25°C. Under these conditions, the distillate is enriched in CFC-115 while the bottom contains essentially pure HFC-125 (>99.5 mole %). The distillate from the second distillation is then fed back into the column and distilled at a pressure of about 210 psia (obtained by heating the reboiler using steam and lowering the condenser coolant flow), a reflux temperature of about 25°C and a reboiler temperature of about 32°C. Upon distillation, the overhead is essentially pure HFC-125 (>97 mole %). CFC-115 (containing about 40 mole % HFC-125) is recovered as the bottom.

25

EXAMPLE 4

To a distillation column, similar to the distillation column of Example 3 is fed crude HFC-125 containing 2 mole % CFC-115 obtained by the hydrofluorination of HCFC-123 with anhydrous hydrogen fluoride in the presence of a chrome oxide catalyst. The distillation is conducted at about 30 psia, a reflux temperature of about -30°C and a reboiler temperature of about -29°C. The overhead is enriched in CFC-115 (5 mole % CFC-115) while the bottom contains essentially pure

HFC-125 (>99 mole %). The distillate is then passed to a second distillation column similar to the first column in structure but operated at high pressure (i.e., about 200 psia), a reflux temperature of about 24°C and a reboiler temperature of about 32°C. At this pressure, the distillate is enriched in HFC-125 (>97 mole %) while the bottoms contain more CFC-115 (>10 mole %). The distillate is then fed to a third distillation column similar in structure to the first column and operated at low pressure (i.e., about 25 psia), a reflux temperature of about -37°C and a reboiler temperature of about -36°C. At this pressure, the distillate is becoming enriched in CFC-115 (about 7 mole %) while the bottoms are richer in HFC-125 (>99 mole %). Finally, the distillate from this third distillation is fed to a fourth distillation column similar in structure to the first column but operated at about 225 psia, a reflux temperature of about 30°C and a reboiler temperature of about 42°C. Under these conditions, essentially pure HFC-125 (>97 mole %) is recovered as distillate while the bottoms are enriched in CFC-115 (>40 mole %).

What is claimed:

1. A process for the purification of a component of a binary azeotrope in which the composition of the azeotrope changes by about 10 mole percent with pressure comprising:

(a) subjecting a binary azeotrope to a distillation step in which most of one of the binary components is removed as distillate (distillate 1) with the bottoms (bottoms 1) enriched in the other component;

(b) subjecting distillate 1 to at least one additional distillation step conducted at a different pressure in which most of the component recovered as bottoms 1 is removed as distillate 2 with the bottoms 2 enriched in the component enriched in distillate 1;

(c) optionally repeating step (b) as many times as desired; and

(d) recovering the desired purified component.

2. A process for the purification of pentafluoroethane comprising:

(a) subjecting a mixture comprising pentafluoroethane and at least about 0.5 mole % chloropentafluoroethane to a distillation step in which most of one of pentafluoroethane or chloropenta-fluoroethane is removed as distillate (distillate 1) with the bottoms (bottoms 1) enriched in the other component;

(b) subjecting distillate 1 to at least one additional distillation step conducted at a different pressure in which most of the component recovered as bottoms 1 is removed as distillate 2 with the bottoms 2 enriched in the component enriched in distillate 1;

(c) optionally repeating step (b) as many times as desired; and

(d) recovering purified pentafluoroethane.

3. The process of claim 2 wherein said distillation is conducted in a single column.


4. The process of claim 2 wherein said distillation is conducted in two separate columns.

5. The process of claim 4 wherein said distillation is conducted as a batch distillation.

-11-

6. The process of claim 4 wherein said distillation is conducted as a continuous distillation.
7. The process of claim 4 wherein step (c) is omitted.
8. The process of claim 7 wherein the first distillation step is conducted at a pressure of at least 50 psia and the second distillation is conducted at a lower pressure.
9. The process of claim 1 wherein said distillation is conducted in a single column.
10. The process of claim 1 wherein said distillation is conducted in two separate columns.
11. The process of claim 10 wherein step (c) is omitted.
12. The process of claim 11 wherein said distillations are conducted at a pressure of less than about 400 psia and greater than about 5 psia.

1 / 1



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

Intern al Application No
PCT/US 94/01117

A. CLASSIFICATION OF SUBJECT MATTER

C 07 C 17/38, C 07 C 19/08, B 01 D 3/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C 07 C 17/00, C 07 C 19/00, B 01 D 3/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	E. BARTHOLOME et al. "Ullmanns Encyklopädie der technischen Chemie", 4th edition, vol. 2, 1992, "Verfahrenstechnik I (Grund- operationen)", VERLAG CHEMIE GMBH, Weinheim, pages 509-510, especially page 509, right column; page 510, left column; fig. 41.	1, 9-11
Y	---	2, 4, 6, 7
Y, P	WO, A1, 93/23 355 (DAIKIN INDUSTRIES LTD.) 25 November 1993 (25.11.93), example 2.	2, 4, 6, 7

☐ Further documents are listed in the continuation of box C.☐ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

05 May 1994

Date of mailing of the international search report

31. 05. 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

KÖRBER e.h.

INTERNATIONAL SEARCH REPORT

-2-

International Application No

PCT/US 94/01117

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP, A1, 0 467 531 (IMPERIAL CHEMICAL INDUSTRIES) 22 January 1992 (22.01.92), page 3, line 48 - page 4, line 9.	1,9-11
Y		2,4, 6,7
Y	WO, A1, 92/20 640 (E.I. DU PONT DE NEMOURS AND COMPANY) 26 November 1992 (26.11.92), page 4, line 14 - page 6, line 17.	2,4, 6,7
A	US, A, 3 505 233 (UNION CARBIDE CORPORATION) 07 April 1970 (07.04.70), claims (cited in the application).	2